

# FEBRUARY 2026

# TOOLS FOCUS

## NEW TO RANGE WORKSHOP ESSENTIALS



Designers and manufacturers of  
Automotive Special Service Tools

**AST6165**

**LOCKING WHEEL NUT/BOLT REMOVAL KIT -  
BMW - FORD - OPEL/VAUXHALL - PSA - VAG  
- VOLVO**

Provides method to remove locking wheel nuts / bolts when specialist key not available.

Simple operation: Select one of 5 adaptor sizes from the kit, locate adaptor on head of nut/bolt, use supplied impact driver to release the locking wheel nut.

Suitable for McGard style locking wheel nuts/bolts.



**AST6189**

**LOCKING WHEEL NUT REMOVAL  
2PC ADAPTOR SET - JAGUAR - LAND ROVER**

**Used with AST6165**

Suitable for locking wheel nuts fitted to **Jaguar**, **Land Rover**, and **Range Rover** applications from 2015 onwards.

Each tool is supplied with an outer shroud and mandrel to suit their specific application.



**AST6259**

**E12 X 140MM CYLINDER HEAD BOLT SOCKET  
PSA 1.0/1.2 'PURETECH' PETROL**

Cylinder Head Bolt Socket is suitable for removal of bolts used on all 1.0 & 1.2 (EB0/EB2) 'Puretech' GDi Petrol engines fitted in **Peugeot**, **Citroën**, **Opel**-**Vauxhall**, and **Toyota** models.

Equivalent to OE tool references: EN-52203, 0109-4.

Also covers **BMW** OE Ref. - 112 250 - M50, M52, M54, S52, M42, M44



**AST5255**

**PETROL 1.2 GDI PURETECH EB2 BELT-IN-OIL ENGINE  
SETTING/LOCKING KIT - CITROËN - PEUGEOT - DS -  
OPEL/VAUXHALL**

Models: **Citroën**: Berlingo IV, C3 Aircross, C3 IV, C4 Cactus, C4 III, C4 Space Tourer/Grand Space Tourer, C5 Aircross, **Peugeot**: 208, 208, 3008, 308, 5008, 508, Partner IV, Rifter, **Toyota**: Proace City/Proace City Verso, **Vauxhall/Opel**: Combo-E (X19)(18-), Combo-E Life (X19)(18-), Crossland X (P17)(17-), Grandland X (A18)(17-)

Equivalent to OE references:

0109-2B, 0109-2C, 0109-2D, 0109-6, 0197-N, EN-52127-2, EN-52588, EN-52809



**AST6170-10**

**LOCKING WHEEL NUT REMOVAL KIT -  
MOULDABLE KEY PACK - SET OF 10**

- Keys feature a **large** and a **small** mouldable end.
- When correctly formed to the locking wheel nut/bolt head pattern a single key can remove **all** locking wheel/bolts from a vehicle.
- For single use, cannot be reformed for use on another vehicle.
- Used with **AST6165** to remove 'McGard' style locking wheel nuts/bolts fitted as OE by over 30 vehicle manufacturers.
- Manufactured by **high quality alloy steel**.



**AST6113**

**HEX SOCKET BIT SET 30PC - 1/2" SQ DRIVE**

Contents:

Length 55mm: H5, H6, H7, H8, H10, H12, H14, H17, H19  
Length 100mm: H5, H6, H7, H8, H10, H11, H12, H13  
Length 140mm: H5, H6, H7, H8, H10, H12, H14  
Length 200mm: H5, H6, H7, H8, H10, H12



**AST6285**

**FUEL INJECTOR REMOVAL SET  
B38 / B48 / B58 / S58 PETROL ENGINES  
BMW - MINI**

Reduces risk of damage to the fuel injectors.

Includes Distance Gauge Tool, ensuring the correct distance between the fuel rail and the injector is maintained.

Equivalent to OE reference: 2 358 417, 2 358 022



**AST6322**

**TX SOCKET BIT SET 32PC - 3/8" AND 1/2" SQ DRIVE**

Contents:

3/8" Sq. Drive  
Length: 55mm: T20, T25, T27, T30, T40, T45  
Length 100mm: T20, T25, T27, T30, T40, T45  
Length 140mm: T40, T45  
Length 200mm: T40, T45

1/2" Sq. Drive  
Length 55mm: T50, T55, T60, T70  
Length 100mm: T50, T55, T60, T70  
Length 140mm: T50, T55, T60, T70  
Length 200mm: T50, T55, T60, T70



[www.asttools.co.uk](http://www.asttools.co.uk)



+44 (0)1527 522550



[sales@asttools.co.uk](mailto:sales@asttools.co.uk)